

FORM-A-FUNNEL®

Safety Data Sheet

1. Product And Company Identification

Product Identifier: FORM-A-FUNNEL

General Use: FORM-A-FUNNEL is a flexible, moldable pouring and draining tool that can easily be molded to create specialized shapes for those hard-to-reach places. Product is great with oil, water, coolants and some solvent. ****Not for use in food preparation****

Product Description: FORM-A-FUNNEL is a aluminum sheet laminated in Nitrile rubber. Comes in colors yellow,green,red.

Company information: Divert-A-Flow Inc.
P.O. Box 554
Roscoe Il. 61073
1-815-623-6576

2. Hazards Identification

GHS Classification: Not a dangerous substance according to GHS

POTENTIAL HEALTH EFFECTS:

Eye Contact: No hazard in normal use of product.

Ingestion: No hazard in normal use of product

Inhalation: No hazard in normal use of product.

Skin Contact: No hazard in normal use of product.

Chronic: Not established

3. Composition/Information on Ingredients

Outer Layer:

CAS: Mixture	Nitrile Rubber (Buna-N)	100%
--------------	-------------------------	------

Inner Layer:

CAS: 7429-90-5	Aluminum	100%
EC: 231-072-3		

4. First Aid Measures

Eye Contact: Not applicable

Ingestion: Not applicable

Inhalation: Not applicable

Skin Contact: Not applicable

5. Fire Fighting Measures

Extinguishing Media: Unused form: Use any means suitable for extinguishing surrounding fire. Used form: that which is compatible to liquid(s) being transferred.

Special Fire Fighting Procedures: In the event of a fire, wear full protective clothing and NIOSH-approved self-contained breathing apparatus with full facepiece.

Hazardous Combustion Products: Not established

Unusual Hazards: Refer to transferred liquid(s) SDS(s).

6. Accidental Release Measures

Spill or Leak Procedures: If material is unused, collect and recover for reuse.

7. Handling and Storage

Handling Precautions: DO NOT CUT FORM-A-FUNNEL. Do not make sharp creases in the material when folding to form a shape.

Storage Precautions: The FORM-A-FUNNEL should be stored flat or rolled up. Maximum temperature: 450°F (232°C). Unaffected in storage by freezing or high temperatures up to 425°F (218°C). Shelf Life: Indefinitely as long as outer layer is not compromised.

General: Store in a cool, dry, ventilated area.

8. Exposure Controls/Personal Protection

Engineering Controls: Appropriate to the material being transferred.

PERSONAL PROTECTION

Eyes: Appropriate to the material being transferred.

Respirator: Appropriate to the material being transferred.

Gloves: Appropriate to the material being transferred.

Other: None

OSHA HAZARDOUS COMPONENTS (29 CFR 1910.1200):

EXPOSURE LIMITS 8 hrs. TWA (ppm)

OSHA PEL

ACGIH TLV

Aluminum	15 mg/m ³ (total)	
	5 mg/m ³ (resp)	10 mg/m ³ (metal dust)

****In its present form, there is little or no dust to present an OSHA hazard****