

# FORM-A-FUNNEL<sup>®</sup>

## Safety Data Sheet

### 1. Product And Company Identification

**Product Identifier:** FORM-A-FUNNEL

**General Use:** FORM-A-FUNNEL is a flexible, moldable pouring and draining tool that can easily be molded to create specialized shapes for those hard-to-reach places. Product is great with oil, water, coolants and some solvent. **\*\*Not for use in food preparation\*\***

**Product Description:** FORM-A-FUNNEL is a aluminum sheet laminated in Nitrile rubber. Comes in colors yellow,green,red.

**Company information:** Divert-A-Flow Inc.  
P.O. Box 554  
Roscoe Il. 61073  
1-815-623-6576

### 2. Hazards Identification

**GHS Classification:** Not a dangerous substance according to GHS

**POTENTIAL HEALTH EFFECTS:**

**Eye Contact:** No hazard in normal use of product.

**Ingestion:** No hazard in normal use of product

**Inhalation:** No hazard in normal use of product.

**Skin Contact:** No hazard in normal use of product.

**Chronic:** Not established

### 3. Composition/Information on Ingredients

*Outer Layer:*

CAS: Mixture	Nitrile Rubber (Buna-N)	100%
--------------	-------------------------	------

*Inner Layer:*

CAS: 7429-90-5	Aluminum	100%
EC: 231-072-3		

### 4. First Aid Measures

**Eye Contact:** Not applicable

**Ingestion:** Not applicable

**Inhalation:** Not applicable

**Skin Contact:** Not applicable

### 5. Fire Fighting Measures

**Extinguishing Media:** Unused form: Use any means suitable for extinguishing surrounding fire. Used form: that which is compatible to liquid(s) being transferred.

**Special Fire Fighting Procedures:** In the event of a fire, wear full protective clothing and NIOSH-approved self-contained breathing apparatus with full facepiece.

**Hazardous Combustion Products:** Not established

**Unusual Hazards:** Refer to transferred liquid(s) SDS(s).

### 6. Accidental Release Measures

**Spill or Leak Procedures:** If material is unused, collect and recover for reuse.

### 7. Handling and Storage

**Handling Precautions:** DO NOT CUT FORM-A-FUNNEL<sup>®</sup>. Do not make sharp creases in the material when folding to form a shape.

**Storage Precautions:** The FORM-A-FUNNEL<sup>®</sup> should be stored flat or rolled up. Maximum temperature: 450°F (232°C). Unaffected in storage by freezing or high temperatures up to 425°F (218°C). Shelf Life: Indefinitely as long as outer layer is not compromised.

**General:** Store in a cool, dry, ventilated area.

### 8. Exposure Controls/Personal Protection

**Engineering Controls:** Appropriate to the material being transferred.

**PERSONAL PROTECTION**

**Eyes:** Appropriate to the material being transferred.

**Respirator:** Appropriate to the material being transferred.

**Gloves:** Appropriate to the material being transferred.

**Other:** None

**OSHA HAZARDOUS COMPONENTS (29 CFR 1910.1200):**

EXPOSURE LIMITS 8 hrs. TWA (ppm)

OSHA PEL

ACGIH TLV

Aluminum	15 mg/m <sup>3</sup> (total)	
	5 mg/m <sup>3</sup> (resp)	10 mg/m <sup>3</sup> (metal dust)

**\*\*In its present form, there is little or no dust to present an OSHA hazard\*\***